



SPECIFICATIONS

MODEL		CK2640SEH	CK2640SEHC	CK3540SE	CK3540SEH	CK3540SEHC	CK4040SE	CK4040SEH	CK4040SEHC
ENGINE									
Engine Gross	HP (kW)	24.5 (18.2)		34.9 (26.0)			39.6 (29.5)		
PTO	HP (kW)	19.0 (14.0)	18.7 (14.0)	30.9 (23.1)	28.9 (21.6)		34.8 (25.9)	33.3 (24.8)	
Displacement	cu. in. (cc)	100.5 (1,647.0)		111.4 (1,826.0)					
Rated Revolution	rpm	2,400		2,600					
Fuel Tank Capacity	gal. (ℓ)	9.0 (34.0)							
DRIVE TRAIN									
Clutch		N/A	N/A	Dry Single Stage	N/A		Dry Single Stage	N/A	
Transmission		Hydrostatic		Manual	Hydrostatic		Manual	Hydrostatic	
Speeds		3-Range		12F x 12R	3-Range		12F x 12R	3-Range	
Differential Lock		Rear Standard							
Brake		Wet Disc							
PTO Type		Independent							
Rear PTO	rpm	540							
Mid PTO	rpm	2,000 (Optional)							
4WD Type		Manual							
HYDRAULIC SYSTEM									
Pump		Gear							
Pump Capacity (Max. Flow Rate)	gpm (L/min)	10.5 (39.6)		11.3 (42.9)					
3-Point Hitch		Category I							
Maximum Lifting Capacity*	lb. (kg)	2,101.0 (953.0)							
Hydraulic Lift Control System		Position							
Number of Standard Remote Vales		2							
Steering		Hydrostatic Power Steering							
TIRE SIZE									
Front AG.		7-16 (28 x 8.5-15/6, 27 x 8.5-15)							
Rear AG.		11.2-24 (41 x 14-20/4, 15-19.5)							
TRAVELING SPEEDS									
Forward	mph (km/h)	0~10.8 (0~17.5)		1.1~16.4 (1.8~26.4)	0~15.7 (0~25.3)		1.1~16.4 (1.8~26.4)	0~15.7 (0~25.3)	
Reverse	mph (km/h)	0~7.6 (0~12.2)		1.1~16.0 (1.7~25.8)	0~11.0 (0~17.7)		1.1~16.0 (1.7~25.8)	0~11.0 (0~17.7)	
DIMENSIONS									
Overall Length w/o Front Weight & w/ 3-pt Hitch	in. (mm)	120.9 (3,070.0)							
Overall Width (Minimum Tread)	in. (mm)	54.5 (1,385.0)							
Overall Height	in. (mm)	92.9 (2,360.0)							
Wheelbase	in. (mm)	65.7 (1,670.0)							
Ground Clearance	in. (mm)	13.4 (340.0)							
Turning Radius (w/Brake)	in. (mm)	107.5 (2,730.0)							
Weight w/AG Tires w/o Weight	lb. (kg)	2,921.1 (1,325.0)	-	-	2,921.1 (1,325.0)	-	-	2,921.1 (1,325.0)	-
Weight w/R14 Tires w/o Weight	lb. (kg)	-	3,492.1 (1,584.0)	3,038.0 (1,378.0)	-	-	3,038.0 (1,378.0)	-	3,509.8 (1,592.0)
Weight w/IND Tires w/o Weight	lb. (kg)	-	-	-	-	3,397.3 (1,541.0)	-	-	-

* @ 24" aft of hitch

NOTE: specifications and design are subject to change without notice.



FRONT END LOADER SPECIFICATIONS

MODEL		KL4040 (NSL)	KL4040 (MSL)
Maximum Lift Height (to Pivot Point)	in. (mm)	98.5 (2,502.0)	98.5 (2,502.0)
Maximum Lift Height Under Level Bucket	in. (mm)	88.0 (2,236.0)	88.0 (2,236.0)
Clearance w/Bucket Dumped	in. (mm)	73.2 (1,860.0)	73.2 (1,860.0)
Reach at Maximum Height	in. (mm)	17.4 (443.0)	17.4 (443.0)
Maximum Dump Angle	deg.	46	40
Reach w/Bucket on Ground	in. (mm)	65.0 (1,651.0)	65.0 (1,651.0)
Maximum Rollback Angle	deg.	40	40
Digging Depth Below Grade	in. (mm)	5.1 (129.0)	5.1 (129.0)
Overall Height (in Carry Position)	in. (mm)	50.3 (1,278.0)	53.1 (1,350.0)
Depth of Bucket (to Back of Inner Shell)	in. (mm)	18.7 (475.0)	18.7 (475.0)
Height of Bucket	in. (mm)	20.1 (510.0)	20.1 (510.0)
Bucket Width	in. (mm)	66.0 (1,677.0)	66.0 (1,677.0)
Lift Capacity to Full Height (at Pivot Pins)	lb. (kg)	1,627.0 (738.0)	1,627.0 (738.0)
Breakout Force (at Pivot Pins)	lb. (kg)	3,384.0 (1,535.0)	3,384.0 (1,535.0)
Bucket Capacity (Heaped)	ft. ³ (m ³)	10.24 (0.29)	10.24 (0.29)

NOTE: specifications and design are subject to change without notice.

BACKHOE SPECIFICATIONS

MODEL		KB4075
Digging Depth (Two Foot Flat Bottom)	in. (mm)	83.4 (2,119.0)
Reach from Center Line of Swing Pivot	in. (mm)	126.4 (3,211.0)
Loading Height (Bucket at 60°)	in. (mm)	75.6 (1,920.0)
Maximum Leveling Angle	deg.	11
Swing Arc	deg.	180
Transport Height (Maximum)	in. (mm)	87.4 (2,219.0)
Transport Overhang	in. (mm)	47.3 (1,201.0)
Bucket Rotation	deg.	177
Stabilizer Spread (Down Position)	in. (mm)	86.0 (2,184.0)
Stabilizer Spread (Up Position)	in. (mm)	46.4 (1,179.0)
Angle of Departure	deg.	17
Shipping Weight (Without Bucket)	lb. (Kgf)	1,314.0 (596.02)
Bucket Digging Force	lb. (Kgf)	2,817.0 (1,278.0)
Dipperstick Digging Force	lb. (Kgf)	2,105.0 (955.0)
Operating Pressure	psi (bar)	2,466.0 (170.0)

NOTE: specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Power Steering
- Rear PTO
- Wet Multi Disc Brakes
- Drawbar
- Parking Brake
- Front Working Lights (Cab)
- Rear Working Light (Cab)
- Deck Mat
- Multi-Function Joystick Valve (SE Models Only)
- Side View Mirror (SE Models 2 Each)
- Telescopic Lower Links (SE Models Only)
- HST Linked Pedal (SE Models Only)
- Dual Remote Hydraulic Valve (Spring/Detent) (SE Models Only)
- RPM Increase for Loader (CK35/CK40 SE Cab Models Only)

OPTIONAL EQUIPMENT

- Front Weights
- Deck Mat
- Mid PTO
- Clevis Type Drawbar
- Side View Mirror (1 Each)
- Fuel Heater Kit (N/A on CK2620)
- Rear Wheel Weight (Ag Tire Only)
- 3rd Function Kit for Front End Loader
- Beacon Light Wiring Kit (SE Cab Models Only)
- RPM Increase Kit for Loader (CK35/CK40 SE Cab Models Only)
- Bluetooth Speaker Kit (SE ROPS Only)
- Dual Remote Hydraulic Valve (Spring/Spring) (Spring/Detent) (Detent/Detent)



SPECIFICATIONS

MODEL		CK2640	CK2640H	CK3540	CK3540H	CK4040	CK4040H
ENGINE							
Engine Gross	HP (kW)	24.5 (18.2)		34.9 (26.0)		39.6 (29.5)	
PTO	HP (kW)	19.5 (14.5)	18.7 (13.9)	30.9 (23.1)	28.9 (21.6)	34.8 (26.1)	33.3 (25.0)
Displacement	cu. in. (cc)	100.5 (1,647.0)		111.4 (1,826.0)			
Rated Revolution	rpm	2,400		2,600			
Fuel Tank Capacity	gal. (ℓ)	9.0 (34.0)					
DRIVE TRAIN							
Clutch		Dry Dual Stage	Dry Single Stage	Dry Dual Stage	Dry Single Stage	Dry Dual Stage	Dry Single Stage
Transmission		Manual	Hydrostatic	Manual	Hydrostatic	Manual	Hydrostatic
Speeds		9F x 3R	3-Range	9F x 3R	3-Range	9F x 3R	3-Range
Differential Lock		Rear Standard					
Brake		Wet Disc					
PTO Type		Live					
Rear PTO	rpm	540					
Mid PTO	rpm	2,000 (Optional)					
4WD Type		Manual					
HYDRAULIC SYSTEM							
Pump		Gear					
Pump Capacity (Max. Flow Rate)	gpm (L/min)	11.3 (42.9)	10.5 (39.6)	11.3 (42.9)			
3-Point Hitch		Category I					
Maximum Lifting Capacity*	lb. (kg)	1,631.0 (739.8)					
Hydraulic Lift Control System		Position					
Number of Standard Remote Vales		2 (Optional)					
Steering		Hydrostatic Power Steering					
TIRE SIZE							
Front AG.		7-16 (28 x 8.5-15/6, 27 x 8.5-15)					
Rear AG.		11.2-24 (41 x 14-20/4, 15-19.5)					
TRAVELING SPEEDS							
Forward	mph (km/h)	0.8~10.6 (1.3~17.1)	0~10.8 (0~17.5)	1.0~15.5 (1.6~24.9)	0~15.7 (0~25.3)	1.0~15.5 (1.6~24.9)	0~15.7 (0~25.3)
Reverse	mph (km/h)	1.0~6.9 (1.6~11.2)	0~7.6 (0~12.2)	1.2~10.1 (2.0~16.3)	0~11.0 (0~17.7)	1.2~10.1 (2.0~16.3)	0~11.0 (0~17.7)
DIMENSIONS							
Overall Length w/o Front Weight & w/ 3-pt Hitch	in. (mm)	120.9 (3,070.0)					
Overall Width (Minimum Tread)	in. (mm)	54.5 (1,385.0)					
Overall Height	in. (mm)	92.9 (2,360.0)					
Wheelbase	in. (mm)	65.7 (1,670.0)					
Ground Clearance	in. (mm)	13.4 (340.0)					
Turning Radius (w/o Brake)	in. (mm)	107.5 (2,730.0)					
Weight w/AG Tires (w/o Weight)	lb. (kg)	2,634.5 (1,195.0)	2,689.6 (1,220.0)	2,678.6 (1,215.0)	2,733.7 (1,240.0)	2,678.6 (1,215.0)	2,733.7 (1,240.0)

* @ 24" aft of hitch

NOTE: specifications and design are subject to change without notice.



FRONT END LOADER SPECIFICATIONS

MODEL		KL4040 (NSL)	KL4040 (MSL)
Maximum Lift Height (to Pivot Point)	in. (mm)	98.5 (2,502.0)	98.5 (2,502.0)
Maximum Lift Height Under Level Bucket	in. (mm)	88.0 (2,236.0)	88.0 (2,236.0)
Clearance w/Bucket Dumped	in. (mm)	73.2 (1,860.0)	73.2 (1,860.0)
Reach at Maximum Height	in. (mm)	17.4 (443.0)	17.4 (443.0)
Maximum Dump Angle	deg.	46	40
Reach w/Bucket on Ground	in. (mm)	65.0 (1,651.0)	65.0 (1,651.0)
Maximum Rollback Angle	deg.	40	40
Digging Depth Below Grade	in. (mm)	5.1 (129.0)	5.1 (129.0)
Overall Height (in Carry Position)	in. (mm)	50.3 (1,278.0)	53.1 (1,350.0)
Depth of Bucket (to Back of Inner Shell)	in. (mm)	18.7 (475.0)	18.7 (475.0)
Height of Bucket	in. (mm)	20.1 (510.0)	20.1 (510.0)
Bucket Width	in. (mm)	66.0 (1,677.0)	66.0 (1,677.0)
Lift Capacity to Full Height (at Pivot Pins)	lb. (kg)	1,627.0 (738.0)	1,627.0 (738.0)
Breakout Force (at Pivot Pins)	lb. (kg)	3,384.0 (1,535.0)	3,384.0 (1,535.0)
Bucket Capacity (Heaped)	ft. ³ (m ³)	10.24 (0.29)	10.24 (0.29)

NOTE: specifications and design are subject to change without notice.

BACKHOE SPECIFICATIONS

MODEL		KB4075
Digging Depth (Two Foot Flat Bottom)	in. (mm)	83.4 (2,119.0)
Reach from Center Line of Swing Pivot	in. (mm)	126.4 (3,211.0)
Loading Height (Bucket at 60°)	in. (mm)	75.6 (1,920.0)
Maximum Leveling Angle	deg.	11
Swing Arc	deg.	180
Transport Height (Maximum)	in. (mm)	87.4 (2,219.0)
Transport Overhang	in. (mm)	47.3 (1,201.0)
Bucket Rotation	deg.	177
Stabilizer Spread (Down Position)	in. (mm)	86.0 (2,184.0)
Stabilizer Spread (Up Position)	in. (mm)	46.4 (1,179.0)
Angle of Departure	deg.	17
Shipping Weight (Without Bucket)	lb. (Kgf)	1,314.0 (596.02)
Bucket Digging Force	lb. (Kgf)	2,817.0 (1,278.0)
Dipperstick Digging Force	lb. (Kgf)	2,105.0 (955.0)
Operating Pressure	psi (bar)	2,466.0 (170.0)

NOTE: specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Power Steering
- Rear PTO
- Wet Multi Disc Brakes
- Joystick Valve
- Drawbar
- Parking Brake
- Front Working Lights (Cab) (SE Models Only)
- Rear Working Light (Cab) (SE Models Only)
- Deck Mat (SE Models Only)
- Side View Mirror (SE Models 2 Each)
- Telescopic Lower Links (SE Models Only)
- HST Linked Pedal (SE Models Only)
- Dual Remote Hydraulic Valve (Spring/Detent) (SE Models Only)
- RPM Increase for Loader (CK35/CK40 SE Cab Models Only)

OPTIONAL EQUIPMENT

- Front Weights
- Deck Mat
- Mid PTO
- Clevis Type Drawbar
- Side View Mirror (1 Each)
- Fuel Heater Kit (N/A on CK2620)
- Rear Wheel Weight (Ag Tire Only)
- 3rd Function Kit for Front End Loader
- Beacon Light Wiring Kit (SE Cab Models Only)
- Bluetooth Speaker Kit (SE ROPS Only)
- Dual Remote Hydraulic Valve (Spring/Spring) (Spring/Detent) (Detent/Detent)