



SPECIFICATIONS

MODEL			K9 2400		K9 2440		K9 2400 Cab	
ENGINE								
Model			3C100LFU-U2				3C100LFU-U3	
Type			3 Cylinder, In-Line Vertical, Water-Cooled Diesel					
Engine Gross		HP (kW)	24.0 (17.9)				24.5 (18.3)	
Rated Revolution		rpm	3,000				3,200	
Displacement		cu. in. (cc)	61.5 (1,007.8)					
Fuel Tank Capacity		gal. (ℓ)	9.8 (37.1)					
DRIVE TRAIN								
Type			Belt CVT				Belt CVT w/Engine Braking	
Gear Range			Low, High, Neutral, Reverse					
Ground Speed		mph (km/h)	0-31 (0-50)					
Brake			Front/Rear Hydraulic Disc					
SUSPENSION								
Front Suspension			Independent, Double A-Arm (Wishbone Type)					
Rear Suspension			Independent, Double A-Arm (Wishbone Type)					
STEERING								
Type			Hydraulic Power				Speed Sensitive Electric Power	
DIMENSIONS / CAPACITY								
Length		in. (mm)	119.7 (3,045.0)		149.2 (3,790.0)		119.7 (3,045.0)	
Width		in. (mm)	62.6 (1,590.0)		62.6 (1,590.0)		65.6 (1,640.0)	
Height		in. (mm)	76.8 (1,950.0)		76.9 (1,955.0)		78.4 (1,990.0)	
Wheelbase		in. (mm)	85.8 (2,180.0)		112.2 (2,850.0)		85.8 (2,180.0)	
Ground Clearance		in. (mm)	12.5 (318.0)		12.0 (304.0)		10.5 (265.0)	
Max. Wheel Tread	Front	in. (mm)	49.8 (1,264.9)				51.9 (1,320.0)	
	Rear	in. (mm)	49.8 (1,264.9)				51.9 (1,320.0)	
Turning Radius		ft. (m)	14.1 (4.3)		18.4 (5.6)		15.1 (4.6)	
Weight (With ATV Tires)		lb. (kg)	2,050.0 (929.9)		2,314.8 (1,050.0)		2,215.0 (1,004.7)	
Towing Capacity		lb. (kg)	1,300.0 (589.7)					
Payload Capacity		lb. (kg)	1,750.5 (794.0)					
Seat Capacity / Style			3 / Bench		5 / Bench		3 / Bench	
CARGO BED								
Length × Width × Depth		in. (mm)	43.7 (1,110) × 58.3 (1,480) × 11.5 (293)		39.2 (1,010) × 58.3 (1,480) × 11.5 (293)		43.7 (1,110) × 58.3 (1,480) × 11.5 (293)	
Bed Capacity		lb. (kg)	1,102.3 (500.0)		661.4 (300.0)		1,102.3 (500.0)	
Dump Box Actuation			Manual with Gas Spring Assist					
TIRE SIZE								
Front	Heavy Duty Worksite		25×10-12					
	Turf		26×9.5-12					
	ATV		25×10-12					
	Tomahawk		25×10-12					
Rear	Heavy Duty Worksite		25×10-12					
	Turf		26×9.5-12					
	ATV		25×11-12					
	Tomahawk		25×10-12					
BODY								
Body Color			Red / Green					

NOTE: specifications and design are subject to change without notice.

K9 SERIES

24 HP UTILITY VEHICLES



STANDARD EQUIPMENT

- Hydrostatic Power Steering
- Front Grill Guard
- Speedometer
- Front Hitch Receiver
- Brake Lights/Turn Signals
- Skid Plates
- Floor Mat
- Suspension Dust Guards
- Muffler Spark Arrestor
- Parking Brake Buzzer
- Spray-In Bed Liner
- Climate Control System (Cab Model)
- Headrest (Cab Model)

OPTIONAL EQUIPMENT

- Laminated Glass Windshield Kit (with Wiper)
- Sun Canopy Kit
- Hydraulic Bed Dump (ROPS Model only)
- Electric Dump Bed (Cab Model Only)
- Remote Hydraulic Kit
- Hand Throttle Kit
- Rear Screen Kit
- Fog Lamp
- Working Lamp
- Side View Mirror
- License Plate Bracket
- Beacon Light Wiring
- Back-Up Alarm
- Aluminum Wheels
- Winch

KIOTI.com

KIOTI Tractor Division • DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 • 877.GO.KIOTI