

TL750 SERIES

74 HP
COMPACT TRACK LOADER



SPECIFICATIONS

MODEL		TL750 Canopy	TL750 Cab	TL750 Flow+
ENGINE				
Model		KIOTI 4HTI4		
Type		KIOTI 4 Cylinder, In-Line Vertical, Water-Cooled 4-Cycle Turbo Diesel, CRDI		
Engine Gross	HP (kW)	73.6 (54.9)		
Rated Revolution	rpm	2,400		
Peak Torque	lbf-ft (N·m)	202 (274) at 1,500 RPMs		
Displacement	cu. in. (cc)	146.8 (2,435.0)		
FUEL CAPACITIES				
Fuel Tank Capacity	gal. (ℓ)	26.4 (100.0)		
Engine Oil (Filter Included)	gal. (ℓ)	2.4 (9.0)		
Engine Coolant (Radiator Included)	gal. (ℓ)	2.7 (10.4)		
Hydraulic Tank	gal. (ℓ)	10.0 (37.9)		
HYDRAULIC SYSTEM				
Hydraulic Flow		Standard		
Loader Hydraulic Pressure	psi (bar)	3,335.9 (230.0)		2,900.0 (200.0)
Loader Hydraulic Flow	gpm (lpm)	21.9 (82.9)		34.0 (128.7)
UNDERCARRIAGE				
Track Width	in. (mm)	15.7 (400.0)		
TRAVEL SPEEDS				
Low	mph (km/h)	4.7 (7.5)		
High	mph (km/h)	7.1 (11.5)		
DIMENSIONS				
Length of Track on Ground	in. (mm)	56.5 (1,435.0)		
Length w/o Bucket	in. (mm)	116.1 (2,950.0)		
Length w/Bucket on Ground	in. (mm)	144.7 (3,675.0)		
Height to Top of Cab (w/o Beacon)	in. (mm)	81.9 (2,080.0)		
Max. Overall Height	in. (mm)	163.8 (4,160.0)		
Hinge Pin Height at Max. Lift	in. (mm)	130.3 (3,310.0)		
Reach at Max. Lift and Dump	in. (mm)	43.2 (1,098.0)		
Clearance at Max. Lift and Dump	in. (mm)	101.8 (2,585.0)		
Ground Clearance	in. (mm)	8.7 (220.0)		
Departure Angle	deg.	25		
Max. Dump Angle	deg.	42		
Vehicle Width	in. (mm)	70.9 (1,800.0)		
Turning Radius from Center – Machine Rear	in. (mm)	67.3 (1,709.0)		
Turning Radius from Center – Coupler	in. (mm)	57.1 (1,450.0)		
Rack Back Angle at Max. Height	deg.	88		
Bucket Pin Reach at Maximum Lift	in. (mm)	23.5 (597.0)		
Width with Bucket (Std)	in. (mm)	74.4 (1,890.0)		
Rack Back Angle on Ground	deg.	29		

NOTE: specifications and design are subject to change without notice.

KIOTI.com

KIOTI Tractor Division • DAEDONG-USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 • 877.GO.KIOTI

TL750 SERIES

74 HP
COMPACT TRACK LOADER



OPERATING SPECIFICATIONS

MODEL		KL2510
Operating Weight w/o Operator (Canopy)	lb. (kg)	9,524.0 (4,320.0)
Operating Weight w/o Operator (Cab)	lb. (kg)	9,689.3 (4,395.0)
Optional Counterweights	lb. (kg)	10,061.9 (4,564.0)
Rated Operating Capacity 35% Tipping Load	lb. (kg)	2,299.4 (1,043.0)
Rated Operating Capacity 50% Tipping Load	lb. (kg)	3,284.9 (1,490.0)
Rated Operating Capacity w/Optional Counterweights	lb. (kg)	2,376.6 (1,078.0)
Tipping Load	lb. (kg)	6,569.8 (2,980.0)
Breakout Force, Tilt (Bucket)	lb. (kg)	5,511.6 (2,500.0)
Breakout Force, Lift	lb. (kg)	5,015.5 (2,275.0)
Traction Force	lbf (kgf)	6,481.6 (2,940.0)
Lift Arm Path		Vertical
Control		ISO Pilot

NOTE: specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- 74 HP KIOTI 2.4L Diesel Engine
- 14-Pin Auxiliary Hydraulic Electrical Connector
- 15.7 in. (400 mm) C-Pattern Rubber Tracks
- 2" Retractable Seatbelt
- 12V Electric Outlet
- Auxiliary Hydraulics
- Backup Alarm
- Battery Disconnect Switch
- Digital Display
- Engine Speed Dial and Pedal
- Excavator Style Overhead Sliding Door
- Horn
- Keyed Engine Start
- LED work lights (2 Front/2 Rear)
- Mechanical Quick Attach
- Open Canopy
- Operator Presence Control
- Pilot Hydraulic Joystick Controls
- Rear View Camera
- Self Leveling
- Suspension Seat
- Two-Speed Travel
- Wet Disc Parking Brake

OPTIONAL EQUIPMENT

- 3" Retractable Seatbelt
- Add-on Counterweights
- Beacon Light
- Bluetooth Radio
- Engine Block Heater
- HVAC
- Polycarbonate Door
- Power Quick Attach
- Flow+ Auxiliary Hydraulics



KIOTI.com

KIOTI Tractor Division • DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 • 877.GO.KIOTI



SPECIFICATIONS

MODEL		SL750 Canopy	SL750 Cab	SL750 Flow+
ENGINE				
Model		KIOTI 4HTI4		
Type		KIOTI 4 Cylinder, In-Line Vertical, Water-Cooled 4-Cycle Turbo Diesel, CRDI		
Engine Gross	HP (kW)	73.6 (54.9)		
Rated Revolution	rpm	2,400		
Peak Torque	lbf-ft (N·m)	202 (274) at 1,500 RPMs		
Displacement	cu. in. (cc)	146.8 (2,435.0)		
FUEL CAPACITIES				
Fuel Tank Capacity	gal. (ℓ)	26.4 (100.0)		
Engine Oil (Filter Included)	gal. (ℓ)	2.4 (9.0)		
Engine Coolant (Radiator Included)	gal. (ℓ)	2.7 (10.4)		
Hydraulic Tank	gal. (ℓ)	10.0 (37.9)		
HYDRAULIC SYSTEM				
Hydraulic Flow		Standard		
Loader Hydraulic Pressure	psi (bar)	3,335.9 (230.0)		2,900.0 (200.0)
Loader Hydraulic Flow	gpm (lpm)	21.9 (82.9)		34.0 (128.7)
UNDERCARRIAGE				
Tire Size		12 x 16.5 12PR Tires		
TRAVEL SPEEDS				
Low	mph (km/h)	7.2 (11.5)		
High	mph (km/h)	12.1 (19.4)		
DIMENSIONS				
Length w/o Bucket	in. (mm)	116.1 (2,950.0)		
Length w/Bucket on Ground	in. (mm)	144.7 (3,675.0)		
Height to Top of Cab (w/o Beacon)	in. (mm)	81.2 (2,063.0)		
Max. Overall Height	in. (mm)	160.2 (4,068.0)		
Hinge Pin Height at Max. Lift	in. (mm)	126.6 (3,215.0)		
Reach at Max. Lift and Dump	in. (mm)	37.4 (949.0)		
Clearance at Max. Lift and Dump	in. (mm)	97.4 (2,473.0)		
Ground Clearance	in. (mm)	7.7 (195.0)		
Departure Angle	deg.	25		
Max. Dump Angle	deg.	42		
Wheelbase	in. (mm)	47.2 (1,200.0)		
Turning Radius from Center – Machine Rear	in. (mm)	70.4 (1,788.0)		
Turning Radius from Center – Coupler	in. (mm)	60.9 (1,548.0)		
Rack Back Angle at Max. Height	deg.	88		
Bucket Pin Reach at Maximum Lift	in. (mm)	16.3 (414.0)		
Width with Bucket (Std)	in. (mm)	74.4 (1,890.0)		
Rack Back Angle on Ground	deg.	29		

NOTE: specifications and design are subject to change without notice.

SL750 SERIES

74 HP
SKID STEER LOADER



OPERATING SPECIFICATIONS

MODEL		KL2510
Operating Weight w/o Operator (Canopy)	lb. (kg)	8,196.7 (3,718.0)
Operating Weight w/o Operator (Cab)	lb. (kg)	8,468.0 (3,841.0)
Optional Counterweights	lb. (kg)	10,061.9 (4,564.0)
Rated Operating Capacity 35% Tipping Load	lb. (kg)	1,882.8 (854.0)
Rated Operating Capacity 50% Tipping Load	lb. (kg)	2,689.6 (1,220.0)
Rated Operating Capacity w/Optional Counterweights	lb. (kg)	2,833.0 (1,285.0)
Tipping Load	lb. (kg)	5,379.3 (2,440.0)
Breakout Force, Tilt (Bucket)	lb. (kg)	5,511.6 (2,500.0)
Breakout Force, Lift	lb. (kg)	5,015.5 (2,275.0)
Traction Force	lbf (kgf)	6,347.2 (2,879.0)
Lift Arm Path		Vertical
Control		ISO Pilot

NOTE: specifications and design are subject to change without notice.



STANDARD EQUIPMENT

- 74 HP KIOTI 2.4L Diesel Engine
- 14-Pin Auxiliary Hydraulic Electrical Connector
- 12 x 16.5 12PR Tires Skid Tires
- 2-inch Retractable Seatbelt
- 12V Electric Outlet
- Auxiliary Hydraulics
- Backup Alarm
- Battery Disconnect Switch
- Digital Display
- Engine Speed Dial and Pedal
- Excavator Style Overhead Sliding Door
- Horn
- Keyed Engine Start
- LED Work Lights (2 Front/2 Rear)
- Mechanical Quick Attach
- Open Canopy
- Operator Presence Control
- Pilot Hydraulic Joystick Controls
- Rear View Camera
- Self Leveling
- Suspension Seat
- Two-Speed Travel
- Wet Disc Brakes

OPTIONAL EQUIPMENT

- 3-inch Retractable Seatbelt
- Add-on Counterweights
- Beacon Light
- Bluetooth Radio
- Engine Block Heater
- HVAC
- Polycarbonate Door
- Power Quick Attach
- Flow+ Auxiliary Hydraulics
- Ride Control

KIOTI.com

KIOTI Tractor Division • DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 • 877.GO.KIOTI