



SPECIFICATIONS

MODEL		ZXS48	ZXS54
ENGINE			
Type		2-Cylinder, 90° V-Twin, Air-Cooled with Internally Vented Crankcase & Carburetor	
Engine Gross	HP (kW)	24.0 (17.9)	
Displacement	cu. in. (cc)	44.3 (726.0)	
Choke		Manual Lever	
Fuel Tank Capacity	gal (ℓ)	7.0 (26.4)	
Fuel Requirement		Unleaded Gasoline (87 Octane or Higher)	
DRIVE TRAIN			
Model		Hydro-Gear ZT-3400	
Displacement (Pump/Motor)	cu. in. (cc)	12 cc / 16 cc	
TIRE SIZE			
Front		13x5-6	
Rear		23x10.5-12	
TRAVELING SPEEDS			
Forward	mph (km/h)	11.0 (17.7)	
Reverse		3.5 (5.6)	
DIMENSIONS			
Overall Length	in. (mm)	65.0 (1,650.0)	
Deck Width (Including Deck Chute)	in. (mm)	60.6 (1,540.0)	68.5 (1,740.0)
Overall Height (Seat Back)	in. (mm)	51.2 (1,300.0)	
Approximate Curb Weight	lb. (kg)	992.0 (450.0)	1,014.0 (460.0)
MOWER DECK			
Mower Deck Type		Fabricated	
Lift Mechanism		Hand Lever with Push Button Transport Release	
Deck Steel Thickness		10-Gauge Dual Plated Steel Deck with 7-Gauge at Edge Area	
Anti-Scalp Ball Rollers		6 (4 front, 2 rear)	
Cutting Width of Mower	in. (mm)	48.0 (1,219.0)	54.0 (1,371.6)
Blades		Notched	
Cutting Height	in. (mm)	1.5-4.5 (38.1-114.3)	
Discharge Chute		Molded Rubber	
Deck Height Adjustment	in. (mm)	Pin	

NOTE: specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Kawasaki FT730V Engine
- Hydro-Gear ZT-3400 Transmission
- 48" (1,219 mm) & 54" (1,372 mm) Decks
- 7.0 Gallon (26 l) Fuel Capacity
- Spring Suspension Operator Platform
- Notched Blades
- Anti-Scalp Rollers
- Cup Holder

OPTIONAL EQUIPMENT

- Mulch Kit
- Anti-Scalp Roller Kit (54" models only)