



SPECIFICATIONS

MODEL		ZX48		ZX54	
ENGINE					
Type		Kawasaki FR651			
Engine Gross	HP (kW)	21.5 (16.0)			
Displacement	cu. in. (cc)	44.3 (726.0)			
Choke		Manual Lever			
Fuel Tank Capacity	gal (ℓ)	4.5 (17.0)			
Fuel Requirement		Unleaded Gasoline (87 Octane or Higher)			
DRIVE TRAIN					
Model		Hydro-Gear® ZT-2800			
Displacement (Pump/Motor)	cu. in. (cc)	2.0 (16.0)			
TIRE SIZE					
Front		13x5-6 Smooth			
Rear		20x10-10 Big Bite			
TRAVELING SPEEDS					
Forward	mph (km/h)	7.5 (12.1)			
Reverse		4.0 (6.4)			
DIMENSIONS					
Overall Length	in. (mm)	79.0 (2,006.6)			
Deck Width (Including Deck Chute)	in. (mm)	58.0 (1,473.2)		67.0 (1,701.8)	
Overall Height (Seat Back)	in. (mm)	47.0 (1,193.8)			
Weight	lb. (kg)	671.0 (304.4)		691.0 (313.4)	
MOWER DECK					
Mower Deck Type		Fabricated			
Lift Mechanism		Foot Pedal			
Deck Steel Thickness		12-Gauge			
Anti-Scalp Ball Rollers		1		3	
Cutting Width of Mower	in. (mm)	48.0 (1,219.2)		54.0 (1,371.6)	
Blades		3 High Lift (Opitonal Mulching)			
Cutting Height	in. (mm)	1.5 (38.1) to 4.5 (114.3)			
Discharge Chute		Side (Durable Plastic)			
Deck Height Adjustment	in. (mm)	0.5 (6.4) by Pin			

NOTE: specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Kawasaki FR615V Engine
- Hydro-Gear ZT-2800 Transaxle
- 12-Gauge Welded Steel Deck
- Big Bite Tires
- Electric PTO
- Hour Meter
- Electric Start
- Hitch Plate
- Engine Guard
- Anti-Scalp Rollers
- High Back Comfort Seat
- Removable Foot Plate
- Cup Holder

OPTIONAL EQUIPMENT

- Mulch Kit
- Bagger
- Arm Rests

KIOTI.com

KIOTI Tractor Division • DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 • 877.GO.KIOTI